



SAFETY DATA SHEET

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : 300V COMPETITION 5W-40

Product code : 13311northamerica

1.2. Relevant identified uses of the substance or mixture and uses advised against

4-stroke engine lubricant

1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL USA, INC.

Address : 5836 Corpore Ave, Suite 150.CA, 90630.Cypress.United States of America.

Telephone : +1 909-625-1292. Fax : +1 909-625-2697.

motul_hse@fr.motul.com

www.motul.com

1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : CARECHEM 24/7 NCEC.

1.5. Other emergency numbers

UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 601 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336

Ireland : +353 1 8092566

24 hours a day, 7 days a week

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

HCS compliant.

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present a health hazard with the exception of possible occupational exposure thresholds (see paragraphs 3 and 8).

2.2. Label elements

HCS compliant.

No labelling requirements for this mixture.

2.3. Other hazards

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification HCS	Nota	%
CAS: 72623-87-1 EC: 276-738-4 REACH: 01-2119474889-13 LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED			15 <= x % < 40
EC: 832-827-5 REACH: 01-2120836642-54 OCTADECENE, REACTION PRODUCTS WITH HEXADECENE, HYDROGENATED	GHS08 Dgr Asp. Tox. 1, H304		15 <= x % < 40
CAS: 64742-54-7 EC: 265-157-1	GHS08 Dgr		1 <= x % < 5

REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	Asp. Tox. 1, H304		
CAS: 72623-86-0 EC: 276-737-9 REACH: 01-2119474878-16 LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED	GHS08 Dgr Asp. Tox. 1, H304		1 <= x % < 5
CAS: 72623-87-1 EC: 276-738-4 REACH: 01-2119474889-13 LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED	GHS08 Dgr Asp. Tox. 1, H304		1 <= x % < 5
CAS: 74869-22-0 EC: 278-012-2 REACH: 01-2119495601-36 MINERAL OIL			1 <= x % < 5



Information on ingredients :

(Full text of H-phrases: see section 16)

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Remove the victim to fresh air. If the symptoms persist, call a physician.

In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.

In the event of splashes or contact with skin :

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

In the event of swallowing :

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

Dry agent, foam, carbon dioxide.

Unsuitable methods of extinction

High volume water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.
Spilled product may make surfaces slippery.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.
Do not swallow
Do not get in eyes, on skin, or on clothing.

Fire prevention :

Prevent access by unauthorised personnel.
Take precautionary measures against static discharges by bonding and grounding equipment.
No smoking.

Recommended equipment and procedures :

For personal protection, see section 8.
Observe precautions stated on label and also industrial safety regulations.
Ensure good ventilation at the workplace

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.
Do not breathe fumes, vapour, spray.

7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place.
Only use hydrocarbon-resistant containers, joints and pipes.

Storage

Keep out of reach of children.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.
Personnel shall wear regularly laundered overalls.

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Type of gloves recommended :

Glove thickness:	0.38 mm	-	-	-	-
Break-through time:	> 480 mn	-	-	-	-

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

No data available.

Physical state

Physical state :	Fluid liquid.
------------------	---------------

Colour

Unspecified

Odour

Odour threshold :	Not stated.
-------------------	-------------

Melting point

Melting point/melting range :	Not relevant.
-------------------------------	---------------

Freezing point

Freezing point / Freezing range :	Not stated.
-----------------------------------	-------------

Boiling point or initial boiling point and boiling range

Boiling point/boiling range :	Not relevant.
-------------------------------	---------------

Flammability

Flammability (solid, gas) :	Not stated.
-----------------------------	-------------

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) :	Not stated.
---	-------------

Explosive properties, upper explosivity limit (%) :	Not stated.
---	-------------

Flash point

Flash Point Interval :	FP > 100°C (212 °F)
------------------------	---------------------

Auto-ignition temperature

Self-ignition temperature :	Not relevant.
-----------------------------	---------------

Decomposition temperature

Decomposition point/decomposition range :	Not relevant.
---	---------------

pH

pH (aqueous solution) :	Not stated.
-------------------------	-------------

pH :

pH :	Not relevant.
------	---------------

Kinematic viscosity

Viscosity :	78.7 mm ² /s à 40°C
-------------	--------------------------------

Solubility

Water solubility :	Insoluble.
--------------------	------------

Fat solubility :	Not stated.
------------------	-------------

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water :	Not stated.
--	-------------

Vapour pressure

Vapour pressure (50°C) :	Not relevant.
--------------------------	---------------

Density and/or relative density

Density :	< 1
-----------	-----

Relative vapour density

Vapour density :	Not stated.
------------------	-------------

 **9.2. Other information**

No data available.

 **9.2.1. Information with regard to physical hazard classes**

No data available.

 **9.2.2. Other safety characteristics**

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from heat and from sources of ignition

Take precautionary measures against static discharges.

10.5. Incompatible materials

Strong oxidants

Acids

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No data available.

11.1.1. Substances

Acute toxicity :

MINERAL OIL (CAS: 74869-22-0)

Oral route :

LD50 > 5000 mg/kg

Species : Rat

Dermal route :

LD50 > 5000 mg/kg

Species : Rat

Inhalation route (n/a) :

LC50 > 5 mg/l

Species : Rat

11.1.2. Mixture

Skin corrosion/skin irritation :

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

Serious damage to eyes/eye irritation :

Mild eye irritation

Aspiration hazard :

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."

May cause lung damage if swallowed

 **11.2. Information on other hazards**

Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 140-88-5 : IARC Group 2B : The agent is possibly carcinogenic to humans.

CAS 5989-27-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

SECTION 12 : ECOLOGICAL INFORMATION

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

MINERAL OIL (CAS: 74869-22-0)

Fish toxicity :

LC50 > 100 mg/l

Species : Pimephales promelas

Duration of exposure : 96 h

Crustacean toxicity :

EC50 > 10000 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

12.1.2. Mixtures

No aquatic toxicity data available for the substances.

12.2. Persistence and degradability

12.2.1. Substances

MINERAL OIL (CAS: 74869-22-0)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-86-0)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC (CAS: 64742-54-7)

Biodegradability :

no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Not very mobile in soil.

The product is insoluble in water and will spread on the surface

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.

SECTION 13 : DISPOSAL CONSIDERATIONS

The appropriate waste management of the mixture and/or its container must be determined in accordance with local regulations.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The following regulations have been used:

- OSHA Hazard Communication Standard 29 CFR 1910.1200

15.2. Container information:

No data available.

15.3. Particular provisions :

No data available.

- Clean Water Act : Toxic Pollutants (CWA 307A)

Unlisted.

- Clean Water Act : Hazardous Substances (CWA 311)

CAS	Name
123-92-2	ISOPENTYL ACETATE

- Clean Water Act : Hazardous Substances (CWA 304b)

Unlisted.

- Clean Water Act : Priority Pollutants (CWA Priority)

Unlisted.

- Clean Air Act : Hazardous Air Pollutants (CAA 112(b) HAP (188))

CAS	Name
140-88-5	ETHYL ACRYLATE

- Clean Air Act : Organic Hazardous Air Pollutants National Emission Standards (CAA 112(b) HON (387))

CAS	Name
140-88-5	ETHYL ACRYLATE

- Clean Air Act : Protection of Stratospheric Ozone (CAA 602)

Unlisted.

- SARA 110

Unlisted.

- SARA 302/304

Unlisted.

- SARA 313

CAS	Name
140-88-5	ETHYL ACRYLATE

- California proposition 65 : Chemicals known to the state to cause cancer or reproductive toxicity

Unlisted.

- Massachusetts : Right to Know

CAS	Name
140-88-5	ETHYL ACRYLATE
123-92-2	ISOPENTYL ACETATE

- New Jersey : Right to Know

CAS	Name
140-88-5	ETHYL ACRYLATE
123-92-2	ISOPENTYL ACETATE

 - Pennsylvania : Hazardous Substance

CAS	Name
140-88-5	ETHYL ACRYLATE
123-92-2	ISOPENTYL ACETATE

 - Rhode Island : Hazardous substance list

CAS	Name
140-88-5	ETHYL ACRYLATE
123-92-2	ISOPENTYL ACETATE

 - TSCA (Toxic Substances Control Act) - USA

CAS	Name
93803-87-3	2-OCTYLDODECYL ISOCTADECANOATE
90901-24-9	MOLYBDENUM,
84605-29-8	BIS[BIS(2-ETHYLHEXYL)CARBAMODITHIOATO-KAPPAS,KAPPAS']DIOXODI-MU-THIOXODI PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS
78-70-6 LINALOOL	
77-83-8	ETHYL 2,3-EPOXY-3-PHENYLBUTYRATE
72623-87-1	LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED
72623-87-1	LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED
72623-87-1	LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED
72623-87-1	LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED
72623-86-0	LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED BASEOIL - UNSPECIFIED
72623-86-0	LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED BASEOIL - UNSPECIFIED
72623-86-0	LUBRICATING OILS (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED BASEOIL - UNSPECIFIED
70693-43-5	1-OCTENE,HOMOPOLYMER, HYDROGENERATED
68037-01-4	DEC-1-ENE, HOMOPOLYMER, HYDROGENATED DEC-1-ENE, OLIGOMERS, HYDROGENATED
64742-70-7	PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED HEAVY
64742-70-7	PARAFFIN OILS (PETROLEUM), CATALYTIC DEWAXED HEAVY
64742-65-0	DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC
64742-65-0	DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC
64742-56-9	DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC
64742-56-9	DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC
64742-55-8	DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC
64742-54-7	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC
64742-54-7	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC
64742-54-7	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC
64742-54-7	DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC
64742-46-7	HYDROCARBONS, C13-C16, N-ALKANES, ISOALKANES, CYCLICS, < 0.03% AROMATICS
63148-62-9	DIMETHYLPOLYSILOXANE
5989-27-5	D-LIMONENE
36878-20-3	BIS(NONYLPHENYL)AMINE
28629-66-5	ZINC BIS(O,O-DISOCTYL) BIS(DITHIOPHOSPHATE)
140-88-5	ETHYL ACRYLATE
123-92-2	ISOPENTYL ACETATE

15.2. Chemical safety assessment

Product is not classified health and environmental hazard. Exposure scenarios are not required.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H304	May be fatal if swallowed and enters airways.
------	---

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.
EC50 : The effective concentration of substance that causes 50% of the maximum response.
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.
STEL : Short-term exposure limit
TWA : Time Weighted Averages
TMP : French Occupational Illness table
TLV : Threshold Limit Value (exposure)
AEV : Average Exposure Value.
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
HCS : Hazard Communication standard (OSHA).