

NOTES

A - Com mon Note	<p>If not separately named, for vehicles with OE-lowered suspension, the dimension of lowering is reduced by the dimension of lowering carried out by manufacturer.</p> <p>If not separately named, vehicles with OE-lifted suspension (e.g. Offroad-Package, Crossover) are excluded from use of our products.</p>																											
	<p>The specifications indicated in the Components Certificate are for the classification of the item / vehicle. Please check the type Components Certificate number of your car and compare with the Components Certificate. (Letter "K" in your vehicle registration certificate or to find at the type plate of your car!)</p>																											
	<p>Please verify before fitting by means of the Components Certificate whether the delivered items (please see marking) are approved for your vehicle (please see area of use). You can find the current Components Certificate on www.eibach.de In case of non-conformance the items must not be fitted – please refer to your dealer.</p>																											
	<p>Mounting - we recommend to have our spring system installed by a qualified workshop only, that has skilled personnel and the required special tools available. - If the installation deviates from the workshop manual, Eibach-Eibach instructions are available online. Mounting position - you can "read" the mounting position of the springs from the imprint - have them installed just the way you read the imprint.</p>																											
	<p>Wheel adjustment - after completion of the spring/suspension installation, checking the wheel adjustment is required. Shock absorbers - if the standard shock absorbers are not fully operative anymore and their efficiency has worn off considerably, we strongly recommend to replace those by new standard shock absorbers or by sports shock absorbers, if using lowering springs. This already can be necessary from 40.000 kilometers OE-damper-mileage.</p>																											
	<p>The installation of Sport-Shock Absorbers is recommended with Sportline springs. As example Bilstein B8 Here all wheel/tyre-combinations are possible, which are released by the wheel type testing institution. The instructions in the wheel Components Certificate have to be adhered to, except for: OE suspension is required.</p>																											
	<p>Depending on engine, gearbox/transmission, equipment and vehicle tolerances lowering may differ from the values given. The dimension of lowering is reduced by the dimension of lowering carried out by manufacturer.</p>																											
	<p>The applicability of our products deals with standard cars. In any case of reconstruction (even with OE-accessory-parts), as the installation of an accessory-brake-system (e.g. ceramic-brakes), sport-suspension, LPG-(liquefied petroleum gas)-system for example, the usage of our products may be excluded. The stated measurements are referring to new standard cars. Measuring points: vertical distance from the middle of the wheel hub to the bottom edge of the mud wing. Generally the stated measurements are nominal values, which can vary depending on every car.</p>																											
	<p>If your vehicle has serial electronic damper control this will not be available anymore while using the B12- or Pro-Street-S-suspension kit. You will see a trouble code. This can be re-programed by an official garage/dealership. If available for your vehicle, we recommend to use Pro-Tronic to avoid the trouble code.</p>																											
7	<p>The spring plates installed by the manufacturer are available at DB specialist workshops in sizes 8-23 mm. This allows to vary the lowering indicated here.</p>																											
9	<p>For tyre equipment 205/50/15 and rim 7J x 15. Recommendation: installation of sports gas pressure shock absorbers of similar construction.</p>																											
10	<p>Part number is available only from our special distributor. Please ask for availability and price.</p>																											
12	<p>For vehicles, not lowered by manufacturer. (OE-sport suspension)</p>																											
15	<p>Not fully equipped.</p>																											
16	<p>The special equipment mentioned below contents following point system:</p> <table border="0"> <tr> <td>air-condition</td> <td>7 points</td> </tr> <tr> <td>automatic-transmission (4+5 Cyl.)</td> <td>4 points</td> </tr> <tr> <td>automatic-transmission (6 Cyl.)</td> <td>2 points</td> </tr> <tr> <td>independent car heating</td> <td>3 points</td> </tr> <tr> <td>sunroof</td> <td>2 points</td> </tr> <tr> <td>ABS</td> <td>2 points</td> </tr> <tr> <td>Airbag</td> <td>1 point</td> </tr> <tr> <td>headlamp cleaning system</td> <td>1 point</td> </tr> <tr> <td>engine skid plate</td> <td>1 point</td> </tr> <tr> <td>electronic seat adjustment</td> <td>2 points</td> </tr> </table> <p>IF THE RESULT IS MORE THAN 4 POINTS ONE HAS TO CHOICE</p> <table border="0"> <tr> <td>up to 7 points</td> <td>8 mm (1 point rubber plate)</td> </tr> <tr> <td>up to 13 points</td> <td>13 mm (2 point rubber plate)</td> </tr> <tr> <td>up to 21 points</td> <td>23 mm (4 point rubber plate)</td> </tr> </table> <p>More than 21 points, the lowering Kit is for this version not possible</p>	air-condition	7 points	automatic-transmission (4+5 Cyl.)	4 points	automatic-transmission (6 Cyl.)	2 points	independent car heating	3 points	sunroof	2 points	ABS	2 points	Airbag	1 point	headlamp cleaning system	1 point	engine skid plate	1 point	electronic seat adjustment	2 points	up to 7 points	8 mm (1 point rubber plate)	up to 13 points	13 mm (2 point rubber plate)	up to 21 points	23 mm (4 point rubber plate)	
air-condition	7 points																											
automatic-transmission (4+5 Cyl.)	4 points																											
automatic-transmission (6 Cyl.)	2 points																											
independent car heating	3 points																											
sunroof	2 points																											
ABS	2 points																											
Airbag	1 point																											
headlamp cleaning system	1 point																											
engine skid plate	1 point																											
electronic seat adjustment	2 points																											
up to 7 points	8 mm (1 point rubber plate)																											
up to 13 points	13 mm (2 point rubber plate)																											
up to 21 points	23 mm (4 point rubber plate)																											
18	<p>Without levelling control.</p>																											
19	<p>Vehicles with 6 cylinder engine require retrofit with sports shocks.</p>																											
20	<p>Except vehicles with 4WD.</p>																											
21	<p>Except electronic suspension systems.</p>																											
22	<p>In combination with Eibach suspension springs or original suspension.</p>																											
23	<p>Front and rear axle height adjustable by threaded strut.</p>																											
24	<p>Front axle height adjustable by threaded strut, rear axle by height adjustable unit.</p>																											
25	<p>In order to ensure sufficient clearance it may be necessary to use wheel spacers if the car is equipped with original wheel sizes.</p>																											
26	<p>When the car is lowered more than 40 mm in combination with a drive shaft diameter more than 42 mm, please make sure that there is sufficient distance between the stabilizer and the drive shaft. It maybe necessary to install another anti-roll bar or other coupling rod.</p>																											
28	<p>Only for vehicles with electronic drive-balance-control.</p>																											
30	<p>Height adjustment only according the measurements indicated in the Components Certificate.</p>																											
32	<p>Except models "Sportive" and Sport (models were are equipped with Bilstein shock absorbers)</p>																											
34	<p>Only for vehicles with front damper diameter of 55 mm</p>																											
35	<p>Only for vehicles with front damper diameter of 50 mm</p>																											
36	<p>For vehicles with EDC additional fitting parts of the manufacturer is necessary: front: BMW-Part-No.: top mount assembly (31 331 091 709 + 31 331 116 983 + 31 331 110 196) rear: BMW-Part-No.: top mount assembly (33 521 091 710 + 33 521 090 282 + 33 521 092 986 + 31 331 137 932 + 33 531 091 031)</p>																											
37	<p>Only front axle height adjustable, rear axle spring and shock absorber</p>																											
38	<p>Only front axle height adjustable, rear axle shock absorber</p>																											
39	<p>For models from 04.2002 onwards the fixation of the piston rod is deepened and covered through a flap (piston rod thread not visible)</p>																											
42	<p>The spring travel dependent brake-pressure regulator at the rear axle has to be inspected and, if necessary, adjusted according to the workshop manual.</p>																											
44	<p>The original rear dampers have to be replaced by the supplied dampers.</p>																											
45	<p>In some cases additional OE-Parts for the installation of the suspension componends are required. Therefore please take a look at the corresponding technical documents which are available on our website.</p>																											
47	<p>The original rear dampers have to be replaced by conventionally dampers.</p>																											
48	<p>In the case of vehicle models with ride height control dampers (mark 2R or 4R) these must be changed to O.E. dampers with mark 1U or 3U, part number: 96 80 99 98, catalogue number: 48 06 443.</p>																											
49	<p>For vehicles with 4WD only!</p>																											
50	<p>Only for vehicles with 51mm front strut clamp.</p>																											
52	<p>Only for vehicles with single leaf spring.</p>																											
53	<p>Only for vehicles with double leaf spring and single leaf with distance part.</p>																											
54	<p>Not for vehicles with ride-height control system. For vehicles with Off-Road Classification only allowed with pass-by-noise less than 75 dB(A) and change of classification to M1.</p>																											
56	<p>Vehicles with combined fog- and running lights have to be checked whether the height of the lower edge of the light is not closer than 350 mm to the ground. In this case additional running lights have to be mounted higher than 350 mm. The original running lights have to be decommissioned by removing the bulbs an the cable connection.</p>																											
58	<p>not suitable for model "Cross"</p>																											
59	<p>Only for vehicles with following characteristics: front axle: steel spring, rear axle: levelling control</p>																											

60	excluded Colt Rallyart up to 2009	
61	strut fixing with screw M14 (4-hole wheel attachment)	
62	strut fixing with screw M16 (5-hole wheel attachment)	
63	from supplement 14	
65	Please check your VIN: this kit fits: 10th character=letter (A, B, ...)	
66	for 5-Seater	
67	for 7-Seater	
68	Increased axle-load when using trailer (see Components Certificate).	
69	If a national individual type Components Certificate exist, it is necessary to approve a modification acceptance according to §19/2 StVZO.	
71	without type: 1.6 Racing (DS3)	
72	Part number is available only from our special distributor. Please ask for availability and price. Contact: Autohaus Haese GmbH, phone: 06134-18290, mail: info-mz@autohaus-haese.de, web: www.autohaus-haese.de	
73	front wheel drive	
74	original spring plate must be used	
75	without AC (Air-Condition)	
76	thread dimension: M12	
77	outer diameter front strut 45 mm	
78	Due to the usage of gas pressure technology of the B6 / B8 dampers the dimension of lowering / lifting may vary slightly vehicle-specifically. Functionality of electronic dampers is not applicable. - If available, we recommend to use Pro-Tronic.	
79	coilspring inner diameter 116mm	
80	coilspring inner diameter 106mm	
81	without 3. row of seats	
82	distance between fixing holes front 58mm	
84	not available for vehicles with xenon headlights (any mounting for the self-levelling headlamp system at the dampers)	
85	thread dimension: M16	
86	short wheel-base	
87	without off-road type	
88	standard suspension	
89	thread dimension: M10	
90	thread dimension: M14	
91	with drum brake	
92	with disk brake	
93	only for vehicles with base axle	
94	only for vehicles with plus axle	
95	only for struts, which are screwed together	
97	without 1BH (Off road package)	
98	with coil spring suspension	
99	outer diameter front strut 47 mm	
101	Once the suspension kit is installed the electronic damper control will not be available anymore. You will see a trouble code. This can be re-programed by an official garage/dealership. If available for your vehicle, we recommend to use Pro-Tronic to avoid the trouble code.	
102	For campmobiles	
103	up to chassis number: 200011 ; up to chassis number: 3B-YE121222	
104	up to chassis number: 3B YE121221	
106	up to chassis number: 41999999	
107	up to chassis number: 48999999	
108	up to chassis number: 4B-Y-200000	
109	up to chassis number: 4D-Y-020000	
110	up to chassis number: 8D-1-030000	
111	up to chassis number: 8D-1-030001	
112	up to chassis number: 8D-X-200000	
113	up to chassis number: 8E-2-400 000	
114	up to chassis number: 8E-5-400 000	
115	up to chassis number: 8E-7-400 000	
116	up to chassis number: A394035	
117	up to chassis number: YS3ES55CD1	
118	for type: Avantgarde	
119	for type: Avantgarde, Elegance	
120	except type: JC Works GP	
121	except type: "IL"	
122	for type: G02	
123	for type: G02, GT, GTI	
124	for type: G07, G08	
125	for type: G07, G08, G09, G11	
126	for type: G07, G08, G09, G11, GT, GTI	
127	for type: G29, G30	
128	for type: M 030	
130	for type: without EDC (electronic damper control)	
131	from chassis number: 199008-> 199209	
132	from chassis number: 199210 ->	
133	from chassis number: 3B-YE121222 ->	
134	from chassis number: 4B-1-000001 ->	
136	from chassis number: 4B-W-070001-> 4B-Y-200000	
137	from chassis number: 4D-1-000 001 ->	
138	from chassis number: 51000001 ->	
139	from chassis number: 8D-1-030000-> 8D-W-006471	
140	from chassis number: 8D-1-030001 ->	
141	from chassis number: 8D-1-030001 ->from chassis number: 200007 ->	
142	from chassis number: 8D-W-006471-> 8D-1-030000	
143	from chassis number: 8D-X-200000 ->	
144	from chassis number: 8D-X-200001-> 8D-1-030000	
145	from chassis number: 8E-2-400001 ->	
146	from chassis number: 8E-5-400 001 ->	
147	from chassis number: 8E-7-400 001 ->	
148	from chassis number: A394035 ->	
149	from chassis number: A394036 ->	
150	from chassis number: F054768 ->	
151	from chassis number: YS3ES55CD2 ->	
153	not for distribution in China (Taiwan)	
154	only in combination with Bilstein Teile-Nr. / part-no. 50-174546 (deactivation module for electronic dampers)- only available at Bilstein: mail: info@bilstein.de / Tel: +49 (0) 23 33 / 7 91-4444	
155	only in combination with BMW part-no. 31 32 1 139 423 (2x) - only available as BMW-OE-parts (stoneguard)	
156	only in combination with BMW part-no. 31 33 1139 436 - only available as BMW-OE-parts (top mount)	
159	without EDC (Electronic Damper Control)	
160	If replacement required: You will find the components in the Components Certificate at the point "Amendment of the vehicle documents". The Components Certificate can be downloaded on: www.eibach.com - click on British flag - Online Catalog / Product & Components Certificate Search (RED BUTTON)	
161	If replacement required: Please contact your dealer. - Please have your car documents, part numbers and sales receipt ready to give detailed information.	
162	Not for "Caddy Maxi"	
163	"LPG-(liquefied petroleum gas)-system"-engines included!	
164	only in combination with BMW part-no. 33 50 6 778 572 (2x) - only available as BMW-OE-parts (stoneguard)	
166	Land of production: Great Britain	
167	up to chassis number: 7L-9-045000	
168	Only for cars with PASM (electronic damper control).	
170	For cars with independent suspension at the rear axle.	
171	For cars with rear live axle.	

174	Not for suspension strut at the rear axle.	
175	For vehicle with electronic damper control. (Series). PRO-TRONIC suppresses the error message after installation of dampers or coil-overs (B12/PSS) without electronic adjustable dampers. The functionality of electronic damper control is not applicable. PLEASE NOTE: If there occur any questions or problems with the PRO-TRONIC, a vehicle-diagnosis-journal is absolute required. Your garage is able to get this journal from your car. Without this journal the handling of your inquiry is not possible.	
176	For vehicle with electronic damper control. (Series). PRO-TRONIC suppresses the error message after installation of the coil-over-suspension (PSS/PSM). The functionality of electronic damper control is not applicable. The kit includes the PRO-TRONIC-unit.	
177	Vehicle with electronic damper control (Series) require the PRO-TRONIC-unit AM65-20-030-01-22. Please order separately.	
178	For "Crosstouran"	
179	Vehicles of the category M1G (Offroad) must be reclassified as M1.	
180	from chassis number: WAUZZZ8...11201	
181	for vehicles without AMG-suspension	
182	for vehicles with AMG-suspension	
183	not for "STI"	
184	Spring plate may be changed! - Kit E8530-140 may require OE-Spring-Plate No. 1HO412341. Kits E8547-140 and E8550-140 may require OE-Spring-Plate No. 357412341A.	
185	up to chassis number: KNEJC524875 644 788	
186	from chassis number: KNEJC524875 644 789	
187	from chassis number: WAUZZZ8...11201	
188	for type: G01, G02, 0N4	
189	for type: G01, G02, 0N1	
190	for type: G03, G04, G05, G06, G07, 0N4	
191	for type: G03, G04, G05, G06, G07, 0N1	
192	Only for vehicles without PASM (electronic damper control).	
193	Only for vehicles without air suspension.	
194	for type: ZFA, not for type 3C3 (USA)	
195	not for type 3C3 (USA)	
196	Damper length: FA: 564 mm, RA: 666 mm	
197	Damper length: FA: 543 mm, RA: 645 mm	
198	Stabilizer diameter 20mm	
199	Stabilizer diameter 21mm	
200	for type: 0N9	
201	for type: 04N	
202	for type: G46, G57, G10	
203	for vehicles with EDC (electronic damper control)	
204	for type: G01, G04, 0N1	
205	for type: G01, G04, 0N4	
206	for type: G01, 0N1	
207	for type: G01, 0N4	
208	for type: G02, 0N1	
209	for type: G02, 0N4	
210	Only Export - nor available in Germany - only without Components Certificate!	
211	long wheel base	
212	Not for "Nürburgring-Edition" (211 HP)	
213	Pigtail-end above	
214	from supplement 13	
215	for vehicles without "OE Offroadpackage"	
216	piston rod - thread M12 - For vehicle without electronic damper control.	
217	piston rod - thread M14 - For vehicle with electronic damper control. (Series). The included blind plug suppresses the error message after installation of the coil-over-suspension (PSS). In some cases an error message occurs in the error memory. - Therefore these blind plugs have been replaced by the new Pro-Tronic-kit AM65-57-004-02-22.	
218	Part number is available only from our special distributor. Please ask for availability and price. Contact: Vmaxx GmbH & Co. KG , phone: +49(0)2103-334929, mail: info@vmaxx.de, web: www.vmaxx.de	
219	Not for "Trailhawk"	
220	Not for "2.0 R WRC"	
221	For vehicles with "Sport-Select-Suspension". Rear axle mount has to be changed. - Please use the included rear axle mount and PRO-TRONIC. PRO-TRONIC suppresses the error message after installation of dampers or coil-overs (B12/PSS) without electronic adjustable dampers. The functionality of electronic damper control is not applicable.	
222	Not for "RS3"	
223	Not for "OPC"/"VXR"	
224	BOM = 1 pc. OE-replacement spring - We recommend always to change both springs of an axle. (2 pc.) To verify the correct spring, please search for the OE-part-No#. (e.g at our website, the TecDoc-cataloge or similar systems)	
225	Not for "T32" (Vehicles with double bolt McPherson strut.) - Only for vehicles with strut-clip.	
226	for type: CBB	
227	for type: CEW	
228	For vehicle with electronic damper control. (Series). Blind-plug-set suppresses the error message after installation of dampers or coil-overs (B12/PSS) without electronic adjustable dampers. The functionality of electronic damper control is not applicable.	
229	Brake disk diameter 266 mm	
230	Brake disk diameter 302 mm	
231	for gasoline engine with manual gearbox	
232	for gasoline engine with automatic gearbox and diesel vehicle	
233	only in combination with BMW part-no. 31 33 1 139 452 - only available as BMW-OE-parts (top mount)	
234	not for "ABC" (Active Body Control)	
235	For vehicle with electronic damper control. (Series). The functionality of electronic damper control will be preserved.	
236	Only for vehicle with S-Line-suspension. (Audi)	
237	Only for vehicle without S-Line-suspension. (Audi)	
238	Only for "T32" - Vehicles with double bolt McPherson strut. - Not for vehicles with strut-clip.	
239	Vehicles with manual transmission	
240	Vehicles with automatic transmission	
241	Vehicles fitted to the HA with two leaf springs per side must be converted to a leaf spring. (For Caddy to Mod.2015 VW Part No. : Leaf spring 2K5 511 151 N; for Caddy from model 2015 VW Part No. 2K5 511 151 AA)	
242	Diameter hole in dome: 33mm	
243	Only for vehicles without Sport Suspension Plus and without DRC - Dynamic Ride Control	
244	Only for vehicles with Sport Suspension Plus including DRC - Dynamic Ride Control	
245	Distribution only by: www.eibach.com.au - Eibach Suspension Technology Pty Limited 3/4 Prosperity Parade Warriewood NSW 2102 Australia	
246	Not for "Tiguan Allspace"	
247	Only for vehicle with Range-Extender.	
248	Not for "CrossCountry"	
249	Not for "Plug-in-Hybrid"	
250	Not for "S3"	
251	Not for "GT3, GT4"	
252	Housing diameter in the clamping area: 49 mm	
253	Housing diameter in the clamping area: 53 mm	
254	Not for vehicles with R.S.-Sportsuspension	
255	Not for 1.6 RS Trophy	
256	for type: G02, G06, G25, G28, G29, G32, 0N4	
257	for type: G01, G02, G03, G04, G06, G25, G28, G29, G32, 0N4	
258	for type: G01, G02, G03, G04, G07, G16, G21, G24, 0N4	
259	for vehicle without AMG-Line Suspension	
260	for vehicle with AMG-Line Suspension	
261	for "Plug-in-Hybrid"	

262	For vehicles with EDC additional fitting parts of the manufacturer is necessary: 31306792211 (coupling rod)	
263	only for Lotus models with Toyota engine	
264	Housing material aluminum	
265	only for cars with 4-doors	
266	Part number is available only from our special distributor. Please ask for availability and price. Contact: Hansen Styling Parts, phone: 04347-706970, mail: info@hansen-styling-parts.de, web: www.hansen-styling-parts.de	
267	not for models with the sales name Wrangler with short wheel base	
268	for cars without direct-shift gearbox (DSG)	
269	for cars with direct-shift gearbox (DSG)	
270	for cars without M1G-Approval	
271	not for R. S. Trophy	
272	Use in 2WD vehicles only in combination with automatic transmission	
273	only for cars with PR-Code 1BV, 2MD, 2MH	
274	only for cars with PR-Code 1BL, 1BQ	
275	front axle up to chassis number: 3603471 / rear axle: without air suspension	
276	front axle up to chassis number: 3603471 / rear axle: with air suspension	
277	front axle from chassis number: 3603472 / rear axle: without air suspension	
278	front axle from chassis number: 3603472 / rear axle: with air suspension	
279	Only for suspension strut at the front axle (McPherson)	
280	not for models with equipment line R-Design	
281	Vehicles without automatic transmission	
282	up to chassis number xxxxxxxxJxxxxxx	
283	not for facelift models	
284	for facelift models	
285	Not for AMG-Models	
286	For BMW models with factory designation F... (eg F20, F30) and electronic damper force adjustment, the acceleration sensor must be properly shut down via the OBD interface. If required, we will let you know the responsible Eibach partner for you. Please contact: Eibach Service Center, sales@eibach.de	
287	not for Audi S4 TDI / MY 05.19 -	
288	not for Audi S5 TDI / MY 05.19 -	
289	Vehicle with electronic damper control (Series) require the PRO-TRONIC-unit AM65-35-029-01-22. Please order separately.	
290	only for cars with PR-Code 0N1	
291	only for cars with PR-Code 0N4	
292	only for cars with PR-Code UC8	
293	only for cars with production date until 25.02.2019 and until FIN (vehicle identification number) digit FIN at position 11 = letter K (production year 2019) FIN at position 12 = letter K (production month February)	17 17 digit
294	Part number is available only from our special distributor. Please ask for availability and price. Squadra Sportiva, http://www.squadra-sportiva.com, e-mail: shop@squadra-sportiva.com / phone: +49 4561-525310	Contact:
295	Delivery only possible via Mitsubishi Germany. If necessary, contact your authorized Mitsubishi dealer.	
296	All petrol engines 2WD/4WD (4-matic) with OE sports suspension with SA950 or SA483 and all 2WD petrol engines with basic suspension SA485	
297	All diesel engines 2WD/4WD (4-matic) with OE sports suspension with SA950 or SA483 and all 2WD Diesel engines with basic suspension SA485	
298	Only for 4WD (4-matic) with basic suspension SA485	
299	Only for cars with Active Drive II	
300	Distance of the mounting holes 58mm	
301	Distance of the mounting holes 72mm	
302	for vehicle variants M and L	
303	only for cars with 2-doors	
304	up to MY 12-2012 only in connection with 2x CV11-5414-AB (OE-part Ford)	
305	for vehicles with a standard empty mass ≤ (less than or equal to) 1700 kg	
306	for vehicles with a standard empty mass > (larger) 1700 kg	
307	wheel base: 2890 mm	
308	not for vehicle with AMG Trail Package	
309	not for vehicles with bump-travel-dependent brake pressure reducers on rear axle (RA)	
310	For following models optionally in connection with M45-20-045-01-01 (7mm) rubber plate on the rear axle: 330e 2WD/xDrive (G20/G21) / BMW 3 M340i xDrive, 330d xDrive, M340d xDrive (G21)	BMW 3
311	without Porsche lift system on the front axle	
312	Fixed setting of the groove adjustment on the rear axle: 2nd ring groove from below	
313	Fixed setting of the groove adjustment on the rear axle: 3rd ring groove from below	
314	for sales name VW T6	
315	for sales name VW T6.1	
316	for sales name VW T6 / VW T6.1	
317	not for vehicles with 19-inch original rims (with and without DCC)	
318	reduced lowering by approx. 15 mm with 19-inch original rims (with and without DCC)	
319	Only vehicles from the Tesla factory in Fremont, USA and VIN (vehicle identification number) 17-digit VIN at position 11 = letter F (Plant of Manufacture = Fremont, California, USA)	
320	not for vehicles with Audi dynamic all-wheel steering	
321	Only vehicles from the Tesla factory in Shanghai, China and VIN (vehicle identification number) 17-digit VIN at position 11 = letter C (Plant of Manufacture = Shanghai, China)	
322	Spacer plates M45-20-045-01-01 included in the scope of delivery are optionally provided for the use of BMW 3 Touring (F31) with a high curb weight (e.g. vehicles with glass roof).	
323	The original Volkswagen rubber plate 5Q0 512 149 G (9mm) or 8J0 512 149 (13 mm) can be used optionally for vehicles with heavy equipment variants (e.g. rear wheel, trailer coupling, glass roof, etc.) - detailed information can be found in the parts certificate. This is an optional exchange for the standard VW rubber plate 5Q0 512 149 F (6mm). Only available from Volkswagen dealers or original parts dealers.	
324	Can only be obtained from Eibach China - eMail: eibach@eibach-china.com. This article does not include any parts certificate!	
325	Different top mounts are used on BMW 5 E34. We recommend the use of following components: 1. top mount 2x 12-248605 2. Following BMW OE parts depending on the year of construction: until MY 04.93: 31336776760 and 31331128524 from MY 04.93: 31332227342 and 31332227348	
326	wheel base: 2755 mm	
327	Depending on the standard chassis, the amount of lowering is reduced by: Code: 0mm 459 Dynamic Body Control / -5mm 485 comfort chassis / -0mm 486 sports suspension / -15mm 677 Agility Control / -15mm	SA- B59 Dynamic Select / -
328	Wheelbase 2670 mm	
329	Not for vehicles with equipment line Wildtrak	
330	Not for "Overland"	
331	Not for vehicles with OE-suspension SA code 459 (Dynamic Body Control - chassis with adaptive dampers)	
332	only for vehicles with OE-suspension SA code 459 (Dynamic Body Control - chassis with adaptive dampers)	
333	Part number is available only at Eibach China. Please ask for availability and price - contact details: Eibach Springs Taicang Ltd., No. 63 Ningbo Road, Taicang 215400 / sales@eibach-china.com, phone: +86 (0) 512 8278 1666, fax: +86 (0) 512 8278 1660	e-Mail:
334	Wheelbase 2785 mm	
335	Wheelbase 2975 mm	
336	only for vehicles with AMG ACTIVE RIDE CONTROL (470) and lift system (479)	
337	Wheelbase 2989 mm	
338	only for vehicles without winch on the front axle	
339	only for vehicles with winch on the front axle	